

GOVOX SERIES

VORTEX SEWAGE PUMPS


- GOVOX series features its vortex impeller coupled with a wide pump casing. The rotation of the impeller produces a whirling, centrifugal action between the impeller and pump casing. The action enables large solids and fibrous matters to be pumped out without obstruction, leading to less impeller wear and longer pump life.
- Guide rail fittings are available on request.

GOVOX 204



GOVOX	204
Outlet	2" (50 mm)
Rated Output	0.4 kW
Shaft Speed	2850 rpm
Solid Passage	32 mm
Height	395 mm
Diameter	Ø 243 mm
Weight	13.5 kg

Also available with float switch (A).




GOVOX 208 315



GOVOX	208	315
Outlet	2" (50 mm)	3" (80 mm)
Rated Output	0.75 kW	1.5 kW
Shaft Speed	2850 rpm	2850 rpm
Solid Passage	37 mm	50 mm
Height	473 mm	501 mm
Diameter	Ø 243 mm	Ø 302 mm
Weight	19.5 kg	24 kg


GOVOX 315 also available in 230 Volt (S).
Also available with float switch (A).



GOVOX-G 322 337 437




GOVOX-G	322	337	437
Outlet	3" (80 mm)	3" (80 mm)	4" (100 mm)
Rated Output	2.2 kW	3.7 kW	3.7 kW
Shaft Speed	2850 rpm	2850 rpm	2850 rpm
Solid Passage	47 mm	52 mm	52 mm
Height	643 mm	643 mm	643 mm
Diameter	Ø 464 mm	Ø 464 mm	Ø 464 mm
Weight	59.5 kg	64 kg	64 kg



GOVOX-G 455 475




GOVOX-G	455	475
Outlet	4" (100 mm)	4" (100 mm)
Rated Output	5.5 kW	7.5 kW
Shaft Speed	2850 rpm	2850 rpm
Solid Passage	52 mm	52 mm
Height	695 mm	717 mm
Diameter	Ø 464 mm	Ø 464 mm
Weight	72.5 kg	75 kg



GOVOX-U 322 337




GOVOX-U	322	337
Outlet	3" (BSP)	3" (BSP)
Rated Output	2.2 kW	3.7 kW
Shaft Speed	2850 rpm	2850 rpm
Solid Passage	55 mm	55 mm
Height	655 mm	712 mm
Diameter	Ø 366 mm	Ø 376 mm
Weight	40 kg	49 kg



GOVOX-U 455 475



GOVOX-U	455	475
Outlet	4" (BSP)	4" (BSP)
Rated Output	5.5 kW	7.5 kW
Shaft Speed	2850 rpm	2850 rpm
Solid Passage	55 mm	55 mm
Height	720 mm	754 mm
Diameter	Ø 376 mm	Ø 389 mm
Weight	60 kg	67 kg



GOVOX-S SERIES VORTEX & AGITATOR PUMPS

- GOVOX-S series pumps are equipped with an agitator, which forcibly agitates the fluid for easy and efficient transmission of sludge, sand, mud, and debris.
- The agitator prevents air lock that tends to take place on vortex pumps.

GOVOX-S 322 337



GOVOX-S	322	337
Outlet	3" (BSP)	3" (BSP)
Rated Output	2.2 kW	3.7 kW
Shaft Speed	2850 rpm	2850 rpm
Solid Passage	13 mm	13 mm
Height	603 mm	660 mm
Diameter	Ø 373 mm	Ø 383 mm
Weight	43 kg	57 kg

